



# ArenaVision MVF403 – world-class performance

## ArenaVision MVF403

ArenaVision MVF403 takes sports floodlighting to the highest level, offering very high light output, optical efficiency, ease of installation, reliability and flexibility. It is ideal for indoor sports halls (1000 W version) as well as many outdoor sports and other lighting applications. The integrated system of oval optics and compact double-ended MHN-LA 1000W or MHN-SA HO 2000W lamps ensures outstanding system efficiency and low glare. A built-in reflector skirt reduces spill light and glare even further. The MHN-SA HO 2000W/956 and MHN-LA 1000W/956 lamps meet the highest international CTV requirements. With the MHN-LA 1000W/842 lamp, the natural colour rendering and comfortable atmosphere are well suited to TV and filming as well as other floodlighting applications. Hot re-strike versions are available for all lamp types, enabling immediate restoration of lighting after power supply failure. The (optional) flicker-free version of ArenaVision MVF403 MHN-LA 1000W is designed to ensure that the flicker effect is fully eliminated in order to guarantee perfect images filmed with super-slow-motion cameras at sports events. The flicker-free version of ArenaVision MVF403 comes equipped with a special electronic igniter, which works in combination with Philips' electronic ballast GearUnits (ECM330), to be ordered separately.

### Benefits

- Innovative floodlights designed around Philips' world-class double-ended lamps; dedicated optics ensure maximum optical efficiency and enable accurate light distribution with a minimum of spill light
- Philips quartz metal-halide lamps meet the most demanding lighting and TV broadcast requirements with excellent colour rendering
- The flicker-free version completely eliminates flicker effect, thereby guaranteeing perfect images filmed with super-slow-motion cameras

# ArenaVision MVF403

## Features

- High-output double-ended metal-halide lamps with excellent colour rendering and lifetime
- Dedicated precision optics
- Safety switch
- Electronic hot-restrike
- Complete Philips lamp, optic and gear system
- Flicker-free light version for super-slow-motion cameras

## Application

- Outdoor sport stadiums
- Indoor sport halls

## Specifications

<b>Type</b>	MVF403
<b>Light source</b>	HID: - 1 x MASTER MHN-SA / XW / 2000 W - 1 x MASTER MHN-LA / XWH / 1000 W
<b>Lamp included</b>	Yes (K or light color 842 or 956)
<b>Optic</b>	Beam category A1 (A1) Beam category A2 (A2) Beam category A3 (A3) Beam category A4 (A4) Beam category A5 (A5) Beam category A6 (A6) Beam category A7 (A7) Beam category A8 (A8)
<b>Optical cover</b>	Front glass for downlighting (DOWN) Uplighting versions (UP) (Not for MHN-2000W version)
<b>Ignitor</b>	Series (SI), 1000 W, 2000W integral Hot-restrike (HRE), integral

## Specifications

<b>Installation</b>	On mast headframe, ceiling, wall and floor mounting The lamp only needs to be installed mechanically; electrical connection achieved by closing the rear cover Precision aiming facilities at both top and bottom of the housing for use in conjunction with the ZVF403 PAD accessory Adjustment of mounting bracket: 360° Ambient temperature outdoor: - MASTER MHN-SA 20000 W lamp version: 35°C (Outdoor only) - MASTER MHN-LA 1000 W lamp version: 45°C (Outdoor and indoor) Drag factor (Cx): 0.93 Projected area in 70° position: 0.20 m
---------------------	--

<b>Options</b>	Aiming memory (AM) to safeguard the original aiming position of the luminaire during servicing Hot re-strike versions enabling immediate restoration of lighting after power supply failure Uplighting versions available for architectural lighting Special cable sleeve version for tropical regions
<b>Materials and finishing</b>	Housing and rear cover: non-corrosive, high-pressure die-cast aluminum Optical cover: chemically toughened glass 3 mm thickness for downlighting versions, ceramic 3 mm thick for uplighting versions Mounting bracket: zinc nickel treated Clips: stainless steel (to secure the back cover) Reflector: anodised and brightened 99.99% aluminum Finishing in raw aluminum

	Max adjustment from the horizontal: -90 / +90°
<b>Maintenance</b>	Lamp access by opening clips of rear cover (tool-less) Equipped with safety switch to cut off current when luminaire is opened (requires additional contactor - supplied by others) No internal cleaning required
<b>Accessories</b>	External louver (ZVF403 GS), precision (ZVF403 PAD) and simple (ZVF403 SAD) aiming devices
<b>Remarks</b>	Equipped with aluminum connection box with series ignitor (SI) Wire mesh to prevent large glass falling out Pre-wired 230 - 240 V / 50 Hz and 380-400-415-430V / 50Hz gear units (ECB/ECP330) are available, to be ordered separately
<b>Main applications</b>	Outdoor sport stadiums, indoor sport halls.


# ArenaVision MVF403

## Versions


ArenaVision MVF403 sports flood-lighting luminaire



## Product details



OPDP\_MVF403i\_0027-Detail photo



Approval and Application	
Mech. impact protection code	IK08
General Information	
CE mark	CE mark
Light source colour	956 daylight
Gear	-
Number of light sources	1
Product Family Code	MVF403
Initial Performance (IEC Compliant)	
Init. Corr. Colour Temperature	5600 K

## General Information

Order Code	Full Product Name	Optical cover/ lens type	Lamp family code	Lamp power	Optic type
59896100	MVF403 MHN-LA1000W/956 A5 ESI	-	MHN-LA	1000 W	Beam category A5
06915700	MVF403 MHN-SA2000W/956 A3 SI	DOWN	MHN-SA	2000 W	Beam category A3
06916400	MVF403 MHN-SA2000W/956 A4 SI	DOWN	MHN-SA	2000 W	Beam category A4

Order Code	Full Product Name	Optical cover/ lens type	Lamp family code	Lamp power	Optic type
06917100	MVF403 MHN-SA2000W/956 A5 SI	DOWN	MHN-SA	2000 W	Beam category A5
06918800	MVF403 MHN-SA2000W/956 A6 SI	DOWN	MHN-SA	2000 W	Beam category A6
06919500	MVF403 MHN-SA2000W/956 A7 SI	DOWN	MHN-SA	2000 W	Beam category A7

