



# HF-Performer II for PL-T/C/R/L/TL5C lamps

## HF-P 1 22-42 PL-T/C/L/TL5C EII 220-240V

HF-Performer EII PL-T/C/R/T5c is a sustainable, slim and high-frequency electronic ballast for a wide range of CFL- ni applications. It is ideal for applications where high energy efficiency is required. The HF-Performer EII range has a robust design, meets all relevant international safety and performance standards and is energy-efficient (CELMA EEI A2).

### Product data

General Information		Operating frequency (nom.)	
Remarks	UK importer address: Signify Commercial UK Limited, 3, Guildford Business Park, GU2 8XG	Operating frequency (nom.)	45 kHz
Application code	EII	Ignition method	Warm Start
Type version	mk4	Crest factor (max.)	1.7
Lamp type	PL-T/C/L/TL5C	Power factor 100% load (nom.)	0.95
Number of lamps	1 piece/unit	Ignition time (max.)	0.52 s
Number of products on MCB (16 A type B) (nom.)	28	Mains voltage performance (AC)	-8%+6%
Automatic restart	Yes	Mains voltage safety (AC)	-10%+10%
Operating and Electrical		Earth leakage current (nom.)	0.5 mA
Input Voltage	220 to 240 V	Inrush current width	0.25 ms
Input frequency	50 to 60 Hz	Constant wattage deviation	-2%/+2%
Operating frequency (max.)	- kHz	Ballast factor (nom.)	1
Operating frequency (min.)	42 kHz	Power losses (nom.)	2.86-2.66 W
		Inrush current peak (max.)	18 A
		Efficiency at full load [%]	91.66 %
		Wiring	
		Connector type input terminals	Insert

## HF-Performer II for PL-T/C/R/L/TL5C lamps

Cable capacity output wires mutual (nom.)	200 pF
Connector type output terminals	Insert
Cable length hot-wiring	0.75 m
Wire strip length	7.5-8.5 mm
Dual fixture master/slave	Not applicable [ Master/Slave oper. not applicable]
Input terminal cross section	0.50-1.50 mm <sup>2</sup>
Output terminal cross section	0.50-1.50 mm <sup>2</sup>
Cable capacity output wires to earth (nom.)	200 pF

### System characteristics

Rated ballast-lamp power	22-42 W
Rated lamp power on PL-T/C	22/42 W

### Temperature

T-ambient (max.)	50 °C
T-ambient (min.)	-25 °C
T storage (max.)	80 °C
T storage (min.)	-40 °C
T-case lifetime (nom.)	75 °C
T-Case maximum (max.)	75 °C
T-Ignition (max.)	50 °C
T-Ignition (min.)	-25 °C

### Emergency Operation

Battery voltage lamp ignition	198-254 V
Battery voltage lamp operation	176-254

### Approval and Application

Energy efficiency index	A2
-------------------------	----

IP classification	IP 20 [ Ingress Protection 20]
EMI 9 kHz ... 30 MHz	EN55015
EMI 30 MHz ... 1,000 MHz	EN55022 level B
Safety standard	IEC 61347-2-3
Performance standard	IEC 60929
Quality standard	ISO 9000:2000
Environmental standard	ISO 14001
Harmonic current emission standard	IEC 61000-3-2
EMC immunity standard	IEC 61547
Vibration standard	IEC68-2-6 F c
Bumps standard	IEC 68-2-29 Eb
Humidity standard	EN 61347-2-3 clause 11
Approval marks	CE marking ENEC certificate VDE-EMV certificate
Temperature marking	Yes
Emergency standard	IEC 60598-2-22
Humming and noise level	Inaudible

### Product Data

Full product code	871150091397530
Order product name	HF-P 1 22-42 PL-T/C/L/TL5C EII 220-240V
EAN/UPC – product	8711500913975
Order code	91397530
SAP numerator – quantity per pack	1
Numerator – packs per outer box	12
SAP material	913700630766
SAP net weight (piece)	0.140 kg

## Dimensional drawing

Product	D1	C1	A1	A2	B1	B2
HF-P 1 22-42 PL-T/C/L/	4.5 mm	30.0	103.0	93.5	67.0	57.5
TL5C EII 220-240V		mm	mm	mm	mm	mm

HF-P 1 22-42 PL-T/C/L/TL5C EII 220-240V

## HF-Performer II for PL-T/C/R/L/TL5C lamps

