



MASTER PL-C 2 Pin



MASTER PL-C 10W/840/2P 1CT/5X10BOX

Energy-saving compact fluorescent lamps Compact long-arc low-pressure mercury discharge lamp Envelope consists of 4 parallel narrow fluorescent tubes

Warnings and Safety

- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap base	G24D-1 [G24d-1]
Life to 10% failures (nom.)	6500 h
Life to 50% failures (nom.)	10000 h
LSF 2000 h Rated	99 %
LSF 4000 h Rated	98 %
LSF 6000 h Rated	92 %
LSF 8000 h Rated	78 %
	Sphere
Light Technical	
Colour Code	840 [CCT of 4,000 K]
Luminous flux (nom.)	600 lm
Luminous flux (rated) (nom.)	600 lm
Colour designation	Cool White (CW)
Chromaticity coordinate X (nom.)	0.38

Chromaticity coordinate Y (nom.)	0.38
Correlated Colour Temperature (Nom)	4000 K
Luminous efficacy (rated) (nom.)	60 lm/W
Colour rendering index (nom.)	80
LLMF 2000 h Rated	92 %
LLMF 4000 h Rated	87 %
LLMF 6000 h Rated	83 %
LLMF 8000 h Rated	81 %

Operating and Electrical

Power (Rated) (Nom)	10.4 W
Lamp current (nom.)	0.190 A

Temperature

Design temperature (nom.)	28 °C
---------------------------	-------

MASTER PL-C 2 Pin

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Cap-base information	2P
----------------------	----


Approval and Application

Energy Efficiency Class	G
Mercury (Hg) content (max.)	1.4 mg
Mercury (Hg) content (nom.)	1.4 mg
Energy consumption kWh/1,000 hours	11 kWh
	423275

Product Data

Full product code	871150070498670
Order product name	MASTER PL-C 10W/840/2P 1CT/5X10BOX
EAN/UPC – product	8711500704986
Order code	70498670
Local order code	10PLC8402PIN
SAP numerator – quantity per pack	1
Numerator – packs per outer box	50
SAP material	927903884040
SAP net weight (piece)	45.000 g
ILCOS code	FSQ-10/40/1B-I-G24d=1


Dimensional drawing




PL-C 10W/840/2P

Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-C 10W/840/2P 1CT/5X10BOX	27.1 mm	27.1 mm	75.5 mm	95.0 mm	117.4 mm

Photometric data



Lightcolour /840



Lightcolour /840

MASTER PL-C 2 Pin

Lifetime



LDLE_PLC2P_0001-Life expectancy diagram

LDLE_PLC2P_0002-Life expectancy diagram



LDLM_PLC2P_0001-Lumen maintenance diagram

