



# MASTER LEDspot MV



## MASTER LED spot VLE D 3.7-35W GU10 930 36D

Delivering a warm, halogen-like accent beam, MASTER LEDspot MV is a perfect fit for spot lighting (track, corridors, lift lobbies, display cases and cabinets) in the hospitality industry. It is particularly suitable to public areas where the light is on 24/7, such as lobbies, corridors, stairwells. MASTER LEDspot MV delivers huge energy savings and minimises maintenance cost without any compromise on brightness, enabling hospitality owners to achieve a return on their investment within one year. These LEDspots are compatible with most existing fixtures with a GU10 holder and designed as a retrofit replacement for halogen or incandescent spots. The dimmable versions drive further efficiencies, while helping to create the desired atmosphere. For environments where the right atmosphere needs to be created (e.g. bars and restaurants), the “DimTone” feature could be useful. This is a LED feature that creates a warmer tone once light is dimmed down to lower intensities.

### Warnings and Safety

- Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights

### Product data

General Information	
Cap base	GU10 [ GU10]
EU RoHS compliant	Yes
Nominal lifetime (nom.)	25000 h
Switching cycle	50,000X
Technical type	3.7-35W Narrow Cone

Light Technical	
Colour Code	930 [ CCT of 3,000 K]
Beam Angle (Nom)	36°
Luminous flux (nom.)	270 lm
Luminous intensity (nom.)	500 cd
Colour designation	White (WH)
Correlated Colour Temperature (Nom)	3000 K
Luminous efficacy (rated) (nom.)	81.08 lm/W
Colour consistency	<6

# MASTER LEDspot MV

Colour rendering index (nom.)	90
LLMF at end of nominal lifetime (nom.)	70 %
Luminous flux in 90° cone (rated)	270 lm

## Operating and Electrical

Input frequency	50 to 60 Hz
Power (Rated) (Nom)	3.7 W
Lamp current (nom.)	20 mA
Wattage equivalent	35 W
Starting time (nom.)	0.5 s
Warm-up time to 60% light (nom.)	0.5 s
Power factor (nom.)	0.8
Voltage (Nom)	220-240 V

## Temperature

T-Case maximum (nom.)	80 °C
-----------------------	-------

## Controls and Dimming

Dimmable	Yes
----------	-----

## Mechanical and Housing

Bulb shape	PAR16 [ PAR 2 inch]
------------	---------------------


## Approval and Application

Energy Efficiency Class	F
Suitable for accent lighting	Yes
Energy consumption kWh/1,000 hours	4 kWh
	400287

## Product Data

Full product code	871869670775300
Order product name	MASTER LED spot VLE D 3.7-35W GU10 930 36D
EAN/UPC – product	8718696707753
Order code	70775300
SAP numerator – quantity per pack	1
Numerator – packs per outer box	10
SAP material	929001348302
SAP net weight (piece)	0.038 kg

## Dimensional drawing





GU10 230V4W-35W 275lm 36D 3000K GU10 Dim

Product	D	C
MASTER LED spot VLE D 3.7-35W GU10 930 36D	50 mm	54 mm


# MASTER LEDspot MV

## Photometric data





MASTER LEDspotMV 35W GU10 930 36D 270lm

MASTER LEDspotMV 35W GU10 930 36D 270lm



MASTER LEDspotMV 35W GU10 36D 260lm

## Lifetime



MASTER LEDspotMV GU10 922-927 36D

MASTER LEDspotMV GU10 922-927 36D

## MASTER LEDspot MV

