



Halogen non-reflector

7027 50W G6.35 12V 1CT/10X10F

Low-voltage quartz halogen capsule lamps

Product data

General Information	
Cap base	G6.35 [G6.35]
Philips code	7027
ANSI Code	BRL-BCD
LIF Code	A1/220
Operating position	S90 [Standing +/-90D or Base Down (BDH)]
Main application	Projection
Life to 50% failures (nom.)	50 h
Light Technical	
Luminous flux (rated) (nom.)	1600 lm
Colour rendering index (nom.)	100
Operating and Electrical	
Power (Rated) (Nom)	50 W
Voltage (Nom)	12 V
Mechanical and Housing	
Bulb material	Quartz-UV Open

Filament shape	Flat
Filament dimensions WxH	3.3x1.6
Luminaire Design Requirements	
Bulb temperature (max.)	900 °C
Pinch temperature (max.)	400 °C
Product Data	
Full product code	871150040982950
Order product name	7027 50W G6.35 12V 1CT/10X10F
EAN/UPC – product	8711500409829
Order code	40982950
Local code	A1220
SAP numerator – quantity per pack	1
Numerator – packs per outer box	100
Material no. (12 NC)	923870217103
SAP net weight (piece)	0.002 kg

Halogen non-reflector

Dimensional drawing



Product	D (max)	L (min)	L (max)	L	P (max)	P	P (min)	C (max)
7027 50W	11.5 mm	29.75	30.25	30	1.05 mm	1 mm	0.95	44 mm
G6.35 12V		mm	mm	mm			mm	
1CT/10X10F								

7027 50W G6.35 12V

