



MASTER PL-L Xtra 4 Pin

MASTER PL-L XTRA 24W/840/4P 1CT/25

Energy-saving compact fluorescent lamps Compact long-arc low-pressure mercury discharge lamp Envelope consists of 2 parallel fluorescent tubes

Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

| General Information | |
|-------------------------------------|--------------|
| Cap base | 2G11 [2G11] |
| Life to 10% failures (nom.) | 14000 h |
| Life to 50% failures (nom.) | 21000 h |
| Life to 50% failures preheat (nom.) | 36000 h |
| System description | na [-] |
| LSF 2000 h Rated | 99 % |
| LSF 4000 h Rated | 99 % |
| LSF 6000 h Rated | 98 % |
| LSF 8000 h Rated | 97 % |
| LSF 12000 h Rated | 95 % |
| LSF 16000 h Rated | 88 % |
| LSF 20000 h Rated | 58 % |
| LSF preheat 2,000 hours rated | 99 % |
| LSF preheat 4,000 hours rated | 99 % |

| LSF preheat 6,000 hours rated | 99 % |
|-------------------------------------|-----------------------|
| LSF preheat 8,000 hours rated | 99 % |
| LSF preheat 16,000 hours rated | 97 % |
| LSF preheat 20,000 hours rated | 94 % |
| Light Technical | |
| Colour Code | 840 [CCT of 4,000 K] |
| Luminous flux (nom.) | 1800 lm |
| Luminous flux (rated) (nom.) | 1800 lm |
| Colour designation | Cool White (CW) |
| Correlated Colour Temperature (Nom) | 4000 K |
| Luminous efficacy (rated) (nom.) | 75 lm/W |
| Colour rendering index (nom.) | 82 |
| LLMF 2000 h Rated | 94 % |
| LLMF 4000 h Rated | 93 % |

MASTER PL-L Xtra 4 Pin

| | |
|--------------------|------|
| LLMF 6000 h Rated | 92 % |
| LLMF 8000 h Rated | 91 % |
| LLMF 12000 h Rated | 90 % |
| LLMF 16000 h Rated | 89 % |
| LLMF 20000 h Rated | 88 % |

Operating and Electrical

| | |
|---------------------|---------|
| Power (Rated) (Nom) | 24.0 W |
| Lamp current (nom.) | 0.345 A |

Temperature

| | |
|---------------------------|-------|
| Design temperature (nom.) | 30 °C |
|---------------------------|-------|

Controls and Dimming

| | |
|----------|-----|
| Dimmable | Yes |
|----------|-----|

Mechanical and Housing

| | |
|----------------------|----|
| Cap-base information | 4P |
|----------------------|----|

Approval and Application

| | |
|------------------------------------|--------|
| Energy efficiency label (EEL) | A |
| Mercury (Hg) content (nom.) | 3.0 mg |
| Energy consumption kWh/1,000 hours | 26 kWh |

Product Data


| | |
|-----------------------------------|------------------------------------|
| Full product code | 871150026770240 |
| Order product name | MASTER PL-L XTRA 24W/840/4P 1CT/25 |
| EAN/UPC – product | 8711500267702 |
| Order code | 26770240 |
| Local code | 24PLL840XTRA |
| SAP numerator – quantity per pack | 1 |
| Numerator – packs per outer box | 25 |
| Material no. (12 NC) | 927907584015 |
| SAP net weight (piece) | 82.000 g |
| ILCOS code | FSD-24/40/1B-E-2G11 |

Dimensional drawing


| Product | D (max) | D1 (max) | A (max) | B (max) | C (max) |
|--|---------|----------|---------|---------|----------|
| MASTER PL-L XTRA 24W/ 840/4P 1CT/25 | 39.0 mm | 18.0 mm | 290 mm | 315 mm | 321.6 mm |

PL-L Xtra 24W/840/4P

Photometric data



Lightcolour /840



Lightcolour /840

MASTER PL-L Xtra 4 Pin

