



MASTER TL5 High Output 90 De Luxe

MASTER TL5 HO 90 De Luxe 49W/950 1SL/20

Low-pressure mercury discharge lamps with a tubular 16 mm envelope

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information		Correlated Colour Temperature (Nom)	
Cap base	G5 [G5]		5200 K
Life to 50% failures preheat (nom.)	30000 h	Luminous efficacy (rated) (nom.)	76 lm/W
LSF preheat 2,000 hours rated	99 %	Colour rendering index (nom.)	92
LSF preheat 4,000 hours rated	99 %	LLMF 2000 h Rated	96 %
LSF preheat 6,000 hours rated	99 %	LLMF 4000 h Rated	95 %
LSF preheat 8,000 hours rated	99 %	LLMF 6000 h Rated	94 %
LSF preheat 16,000 hours rated	97 %	LLMF 8000 h Rated	93 %
LSF preheat 20,000 hours rated	84 %	LLMF 12000 h Rated	92 %
		LLMF 16000 h Rated	91 %
		LLMF 20000 h Rated	90 %
Light Technical		Operating and Electrical	
Colour Code	950 [CCT of 5,000 K]	Power (Rated) (Nom)	49.2 W
Luminous flux (nom.)	4200 lm	Lamp current (nom.)	0.255 A
Luminous flux (rated) (nom.)	3725 lm		
Colour designation	Daylight	Temperature	
Luminous Efficacy (@ Max Lumen, Rated) (Nom)	85 lm/W	Design temperature (nom.)	35 °C
Chromaticity coordinate X (nom.)	346		
Chromaticity coordinate Y (nom.)	359		

MASTER TL5 High Output 90 De Luxe

Controls and Dimming

Dimmable	Yes
----------	-----

Approval and Application


Energy efficiency label (EEL)	A
Mercury (Hg) content (nom.)	1.4 mg
Energy consumption kWh/1,000 hours	54 kWh

Product Data

Full product code	871150089062700
Order product name	MASTER TL5 HO 90 De Luxe 49W/950 1SL20

EAN/UPC – product	8711500890627
Order code	89062700
Local code	49950
SAP numerator – quantity per pack	1
Numerator – packs per outer box	20
Material no. (12 NC)	927991595024
SAP net weight (piece)	127.400 g
ILCOS code	FDH-49/50/1A-L/P-G5-16/1450


Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HO 90 De Luxe 49W/950 1SL20	17 mm	1449.0 mm	1456.1 mm	1453.7 mm	1463.2 mm

TL5 HO 49W/950

Photometric data




Lightcolour TL5 /950



Lightcolour TL5 /950


MASTER TL5 High Output 90 De Luxe

Lifetime



LDLE_TL5-HO9_0001-Life expectancy diagram

LDLE_TL5-HO9_0002-Life expectancy diagram



LDLM_TL5-HO9_0001-Lumen maintenance diagram

